

<b>Film Type</b>	<i>Clear Single Pane</i>	<i>Clear Dual Pane</i>	<i>Tinted Single Pane</i>	<i>Tinted Dual Pane</i>	<i>Low-E Dual Pane</i>	<i>Clear Laminated</i>	<i>Tinted Laminated</i>	<i>Low-E Laminated</i>
IRis 70	1	2	2	2	2	3	4	4
Geo 30	1	2	2	2	2	3	4	4
Geo 40	1	1	2	2	2	3	3	3
Geo 50	1	1	2	2	2	3	3	3
Super Alloy 15	1	1	2	2	2	3	3	3
Super Alloy 25	1	1	2	2	2	3	3	3
Pronano 70	1	2	2	2	2	3	4	4

**Glass Type**

<i>Annealed</i>	3	<b><u>Total Score (Film + Glass)</u></b>
<i>Heat Stengthend</i>	2	<i>4 or less      Preapproved for Seal Failaure and Glass Breakage</i>
<i>Tempered</i>	1	<i>5 or more      Not Approved for Seal Failaure and Glass Breakage without manufactures exemption</i>

**No Warranty if any of these restricted applications are present:**

- Double pane/ insulated glass units with surface 3 low-e coating
- Skylights
- Buildings with previous glass breakage or seal failure history
- Any glass with pre-existing window film
- Improperly sealed or installed windows
- Any non glass windows
- Any insulated gas units greater than 2 panes
- Single pane windows larger than 100 square feet
- Double pane windows larger than 40 square feet
- Ornamented glass
- Glass thicker than ¼ inch
- Partial film installation
- Damaged glass
- Wired, textured or patterned glass
- Glass with defective sealant or gaskets
- Exterior shading of less than 25% of the total glass area and greater than 25% of the perimeter
- Broken glass or insulated gas units with seal failure prior to installation
- Concrete framing
- Metal framing systems with no gaskets or seals
- Installations over 2,500 square feet require preapproval